

Ahlstrom-Munksjö Nano GT

Pulse-jet filtration media for gas turbines operating with fine pollution.

Quality of air entering the turbine is a significant factor in the performance and lifetime of the gas turbine. Ahlstrom-Munksjö offers a complete range of filtration media developed for gas turbine applications, to meet specific market needs in various operational environments.

Ahlstrom-Munksjö **Nano GT** portfolio is based on our market reference CellTech GT or Synthetic GT corrugated filtration media, but coated with electrospun nanofibers on the upstream side.

With a self-supported structure, it combines leading performance in pleatability, with optimal mechanical filtration at low pressure drop and excellent self-cleaning behaviour, even with fine pollution.

Ahlstrom-Munksjö **Nano GT** delivers excellent protection of the gas turbine and long life time for both dry and wet environments.

Benefits

- ✔ **Offers ePM1 80% (ISO16890) efficiency** – delivering excellent protection of gas turbine against fine dust.
- ✔ **Delivers lowest level of pressure drop** – minimizing energy consumption.
- ✔ **Optimal back-pulsing behaviour** – delivering longer time between service intervals.
- ✔ **Covers dry & wet environmental conditions** – available with CellTech and Synthetic corrugated base media, offering ideal performance for pleatability and durability.

Ahlstrom-Munksjö Nano GT

Nano GT offering is reaching F9 (EN779:2012) / ePM1 80% (ISO16890) at very low pressure drop. It delivers up to 4 times more particulate removal of submicron particles (PM1) than a more traditional M5 material without significant increase of pressure drop, making it our recommended option for environments with fine pollution. Additionally, the nano layer supports very good pulse-jet cleaning behavior, due to predominant surface filtration phenomena.

NP70 is our main **Nano GT** reference designed for dry environment, combining a CellTech GT base media (cellulose/polyester fiber blend, treated with water repellent chemistry) with a nano layer, delivering consistent behavior along the filter life time.

AK4560NANCS2WR is our main **Nano GT** reference designed for humid environment, combining a Synthetic GT base media (full synthetic fiber blend, treated with water repellent chemistry) with an upgraded nano layer, delivering excellent performances and durability even in high humidity conditions.

Both **Nano GT** references have a deep corrugation which guarantees excellent processing on rotary pleaters and enhanced pleat stability. Flame retardant feature technically available on demand.

Ahlstrom-Munksjö Nano GT – Key Grade Characteristics

Grades	Media Design	Basis Weight	Efficiency Class		Thickness	Corrugation Depth	Air Permeability	MD Stiffness
		g/m ²	EN779-2012	ISO16890	µm	µm	L/m ² /s @200 Pa	g
NP 70	Cellulose/synthetic + nanofibers	120	F9	ePM1 80%	320	440	145	4.0
NP 70 FR	Cellulose/synthetic FR (F1) + nanofibers	130	F9	ePM1 80%	360	450	110	3.7
AK4560NANCS2WR	100% synthetic + nanofibers	117	F9	ePM1 80%	620	430	239	1.9

Contact Ahlstrom-Munksjö Sales: ✉ filtration@ahlstrom-munksjo.com

www.ahlstrom-munksjo.com



Disclaimer: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability of fitness for use. All users of the material are responsible for ensuring that it is suitable for their needs, environment and end use. All data is subject to change as Ahlstrom-Munksjö deems appropriate.